



EP 06246
Europäisches
Patentamt

06246
European
Patent Office

09/06439
Office européen
des brevets

EPO - Munich
17
26. Aug. 1999

REC'D 15 OCT 1999

WIPO PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

98250316.1

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

Aslette Fiedler

A. Fiedler

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

15/07/99

Best Available Copy

This Page Blank (uspto)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation

Anmeldung Nr.:
Application no.: 98250316.1
Demande n°:

Anmeldetag:
Date of filing: 07/09/98
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
DEUTSCHE THOMSON-BRANDT GMBH
78048 Villingen-Schwenningen
GERMANY

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Time stamping in bitstream recording

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

This Page Blank (uspto)

1 Introduction of Stream Recording Format

1.1 Purpose of the Specification

This DVD Stream Recording Specification is defined to use rewritable DVD discs for recording existing digital bitstreams, editing them and playing them back as bitstreams. The Specification is designed to satisfy the following requirements:

1.1.1 Service Requirements

1.1.1.1 Individual Packet Size Support

Any packet size should be supported as long as it is less than 2kByte and of constant length within a take.

1.1.2 Timing Regeneration

A timing mechanism (time stamp) needs to be added to every broadcast packet to enable proper packet delivery during playback.

1.1.1.3 Non-real-time recording/download

To enlarge the fields of applications, non-real-time recording should be possible. However, in this case the STB has to generate the Time Stamp information.

1.1.1.4 Data allocation strategy

Data allocation strategy and file system need to be designed to support real-time stream recording. The solution, which will be specified in the RTRW activity, should be studied and adopted as close as possible.

1.1.1.5 TOC and Service Information Support

Many digital services require Service Information which normally is embedded in the real-time stream. To support the STB, DVD should provide additional space, which can be used by the STB to duplicate part of the service information and to add additional TOC information.

1.1.1.6 Copy Protection Support

The Copy Protection rules are discussed in CPTWG and WG9. These rules must be supported. In addition any scrambling performed by the service provider or the STB must be kept unchanged. In a later stage some joint discussion with SW owners and service providers might be needed.

1.1.2 User Requirements

User requirements can be grouped into requirements for recording, requirements for playback, and requirements for editing.

(Requirements for Recording)

1.1.2.1 Real-time Recording

The format should be designed to enable real-time recording of digital streams. It also should allow the user to concatenate recordings, even if those recordings consist of

~~DVD Stream Recording~~

2

~~THOMSON multimedia Confidential 2~~

different stream formats. If recordings are concatenated, a (close to) seamless playback possibility would be nice but is not required.

1.1.2.2 Total Recording Time

Regarding the recording time, the conditions are very similar to the RTRW scenario. Therefore the same rules should be valid. In any case the user must be able to understand the situation and to take appropriate action, if needed.

1.1.2.3 Navigation Support

To support navigation two pieces of information (lists) should be generated during recording.

An 'original' version of a play list. This list contains quite low level information, e.g. time map or (broadcast) packet order of the recording. This list is accessible by the STB and the content is understood by the DVD streamer as well as by the STB. In its 'original' version the playlist enables the playback of a complete recording. The playlist may be accessed and extended after recording by the STB to allow more sophisticated playback sequences.

The second piece of information, mapping list, is generated to support the stream recorder to retrieve packet stream chunks (cells), that are described in terms of the application domain (e.g. 'broadcast packets' or 'time'). This list is owned and understood by the DVD streamer only.

1.1.2.4 Content Description

The format should reserve space, which can be used by the STB to store high level TOC and Service Information. This information is provided for the user to navigate through the content stored on disc and may contain sophisticated GUI information. The content is not needed to be understood by the stream recorder. However a common subset of the TOC information, e.g. based on a character string, may be useful to be shared between STB and DVD, in order to enable the stream recorder to provide a basic menu by itself. This may require some joint discussion with STB manufacturers.

(Requirements for Playback)

1.1.2.5 Playback of individual recordings

Needs to be supported; should be possible via play list.

1.1.2.6 Playing all recordings sequentially

This is basically a set matter; should be possible via playlist.

1.1.2.7 Player menus for entry point selection

This is mainly STB's responsibility, which can generate a sophisticated menu based on the TOC information stored on the disc. However, it should be possible to generate a simple menu by the streamer itself, e.g. via some 'character' information which is shared by STB and DVD.

1.1.2.8 Trick play modes

The STB should be able to steer trick play via the 'play list'. Due to the nature of the broadcast stream, the trick play features may be limited to basic ones, e.g. Time Search and Title Jump.

~~DVD Stream Recording~~

3

~~THOMSON multimedia Confidential 7~~**1.1.2.9 User defined PB sequences**

Features like playback programming or parental control can be supported via the play list

1.1.2.10 Play list support

The playlist must be supported as a key for all special playback and navigation.

1.1.2.11 Play list creation

The DVD streamer should create the 'original version' of the play list. It also should allow extensions and modifications of the play list by the STB for more sophisticated playback features. The DVD streamer is not responsible for the content of those sophisticated playlist(s).

(Requirements for Editing)

2.12 Delete single recordings

The format must support the deletion of single recordings on user's request

1.1.2.13 Delete parts of recordings

If possible, the format should allow this feature under the control of the STB. However, complex processing and knowledge on the service may be required for this functionality.

1.1.2.14 Inserting

If possible, the format may support insert editing. This feature will probably require very complex processing and deep understanding of the service. An implementation, which will allow this feature, may be of semi-professional nature.

~~DVD Stream Recording~~~~THOMSON multimedia Confidential ?~~

4

1.2 System Model

This specification is based on the following overall system model:




Figure 1-1 Overall System Model of DVD Stream Recording

<Stream Data & Navigation Data>

1.3 Directory and File Structure

The organization of Stream Data and Navigation Data of DVD Stream Recording is done in a specific way such as to take into account the following:

- Any DVD Streamer Device has certain requirements to store its own "housekeeping" data on the disc. These data are solely for helping the retrieval of recorded data; they need not be understood or even be visible to any outside Application Device.
- Any DVD Streamer Device needs to communicate with the Application Device it is connected to. This communication should be straightforward, and as universal as possible, so that the maximum possible range of applications - both today and future - can be connected to the Streamer. The Navigation Data to support such communication must be understandable by the Streamer as well as by the Application Device.

The Streamer Device should offer to the connected Application Device a means for storing its own private data of any desired kind. The Streamer needs not to understand any of the content, internal structure, or meaning of this "Application Private Data".

Figure 1-2 illustrates the directory and files where all the data comprising the disc content according to this Specification are recorded. All the files storing the disc content are placed under the STRREC directory.




Figure 1-2 Directory and File Configuration

Under the STRREC directory, the following files are created:

- **COMMON.IFO**

Basic information to describe the stream content. Needs to be understood by the Application Device as well as the Streamer.

- **STREAMER.IFO**

Private housekeeping information specific to the Streamer Device. Needs not to be understood by the Application Device.

- **APPLICAT.IFO**

Application Private Data, i.e. information that is specific to the Application(s) connected to the Streamer. Needs not to be understood by the Streamer.

~~DVD Stream Recording~~

6

~~THOMSON multimedia Confidential?~~

• **REALTIME.SOB**

Recorded real-time stream data proper.

Note that except for the files described above, the STRREC directory shall not contain any other files or directories.

~~DVD Stream Recording~~~~TS 3 3/26/1998~~~~THOMSON multimedia Confidential~~

7

2 Navigation Data Structure

Navigation data is provided to control the recording, playing back, and editing of any bitstreams that are recorded according to this Specification. As shown in Fig. 2-1, Navigation Data consists of Stream Management Information (SMI) as contained in the file named COMMON.IFO and of Housekeeping Information (HKPI) as contained in the file named STREAMER.IFO.

From the point of view of the Streamer Device, these two kinds of information are sufficient to perform all necessary operations. Their details are described in Section "2.1 Streamer Relevant Navigation Data" below.




Figure 2-1 Structure of DVD Streamer Navigation Data

In addition to these, DVD Stream Recording also foresees the possibility of reserving a storage location for Application Private Data (APD), which may in general also be considered as Navigation Data. See Section "2.2 Application Private Data" for Details.

2.1 Streamer Relevant Navigation Data

As explained above, SMI and HKPI are the Navigation Data which are directly relevant for the Streamer operation.

SMI consists of three kinds of information tables, namely Stream Manager General Information (SM_GI), Stream Title Table (STT), and Stream Playlist Table (SPLT). These three tables shall all mandatorily be recorded and stored in the COMMON.IFO file in this order.

HKPI consists of two kinds of information tables, namely Housekeeping General Information (HKP_GI) and Housekeeping Address Table (HAT). Both shall mandatorily be recorded and stored in the STREAMER.IFO file in this order.

NB: Unlike in the "DVD Specification for Read-Only Disc Part 3 VIDEO SPECIFICATION", where each table within Navigation Information shall be aligned on a sector boundary, there is no such restriction in Stream Recording.

DVD Stream Recording

THOMSON multimedia Confidential

2.1.1 Stream Manager General Information (SM_GI)

RBP		Contents	Number of Bytes
0 to 9	STRMG_ID	STRMG Identifier	10
10 to 11	reserved	reserved	2
12 to 15	SMI_EA	End address of SMI	4
16 to 27	reserved	reserved	12
28 to 31	SMGI_EA	End address of SM_GI	4
32 to 33	VERN	Version number of DVD Streamer Specifications	2
34 to 127	reserved	reserved	94
128 to 129	TM_ZONE	Time Zone	2
130 to 191	reserved	reserved	62
192 to 195	STT_SA	Start Address of STT	4
196 to 199	SPLT_SA	Start Address of SPLT	4
200 to 511	reserved	reserved	312
Total			512

(RBP 0 to 9) STRMG_ID

Describes "DVD_STR_MG" to identify Stream Recording Management Information File with character set code of ISO646 (a-characters).

(RBP 12 to 15) SMI_EA


Describes the end address of SMI with RBN from the first LB of this SMI.

(RBP 28 to 31) SMGI_EA

Describes the end address of SM_GI with RBN from the first byte of this SM_GI.

(RBP 32 to 33) VERN

Describes the version number of this Specification.



Book Part version ... 0000b 0001b: version 0.1
Others: reserved

(RBP 128 to 129) TM_ZONE

Describes the Time Zone for this Disc. All fields related to "Recorded Time" share this Time Zone value. The detailed structure for TM_ZONE is TBD.

(RBP 192 to 195) STT_SA

Describes the start address of STT with RBN from the first byte of this SM_GI.

(RBP 196 to 199) SPLT_SA

Describes the start address of SPLT with RBN from the first byte of this SM_GI.

2.1.2 Stream Title Table (STT)




Figure 2-2 : Stream Title Table

2.1.2.1 Stream Title Table General Information (STT_GI)

	Contents	Number of Bytes
(1) ST_Ns	Number of Stream Titles	2
(2) STT_EA	End Address of Stream Title Table	4
(3) STN_CHRS	Stream Title Name Character Set	1
	Total	7

(1) ST_Ns

Describes the number of Stream Titles, which are described in this STT. The maximum allowable number of Stream Titles is 999.

(2) STT_EA

Describes the End Address of Stream Title Table with RBN from the first byte of the STT.

(1) STN_CHRS

Identifies the character set used for the Stream Title Names (STNs) in this STT. Details are TBD.

2.1.2.2 Stream Title Entry (STE)

	Contents	Number of Bytes
(1) AP_PKT_SZ	Application Packet Size	2
(2) SRV_ID	Service ID	1
(3) AP_DEV_ID	Application Device ID	12
(4) ST_DUR	Stream Duration	6
(5) ST_NM_SRP	Stream Name Search Pointer	4
	Total	25

(1) AP_PKT_SZ

Describes the Application Packet Size in bytes. This packet size is valid for the entire stream title.

NB: Due to the minimum transfer rate restriction rules described in Section „??“, knowledge of the AP_PKT_SZ does not automatically and not for all streamer packets imply how many application packets are grouped together into the streamer packet.

(2) SRV_ID

Describes an identifier of the digital service which created the stream of this title. Details of the identifier are TBD.

(3) AP_DEV_ID

Describes an identifier of the application device that was physically delivering the stream of this title. Details of the identifier are TBD.

(4) ST_DUR

Describes the duration of the stream of this title, as resulting from the difference between the extended SCR of the last application packet of the stream minus the extended SCR of the first application packet of the stream. For the definition of Extended SCR, see Section „??“.

(5) ST_NM_SRP

Describes the start address of the name string associated with this stream title, with RBN from the first byte of the STT. Name sharing shall not occur, i.e. each of the ST_NM_SRPs of the stream titles shall point to a different stream title name.

2.1.2.3 Stream Title Name (STN)

	Contents	Number of Bytes
(1) ST_NAME	Stream Title Name	variable

(1) ST_NAME

Describes the Stream Title Name as a variable length string of characters from the character set identified by STN_CHRS of STT_GI.

2.1.3 Stream Playlist Table (SPLT)




Figure 2-3 : Stream Playlist Table

2.1.3.1 Stream Playlist Table General Information (SPLT_GI)

	Contents	Number of Bytes
(1) SPL_Ns	Number of Playlists	1
(2) SPLT_EA	End address of SPLT	4
(3) SPLN_CHRS	Stream Playlist Name Character Set	1
	Total	6

(1) SPL_Ns

Describes the Number of playlists described in this SPLT. The maximum allowed number of playlists is 99. SPL_Ns also informs, how many SPI_SA and associated SPI are included in this SPLT.

(2) SPLT_EA

Describes the End Address of this SPLT with RBN from the first byte of this SPLT.

(3) SPLN_CHRS

Identifies the character set used for the Stream Playlist Names (SPLNs) in this SPLT. Details are TBD.

2.1.3.2 Stream Playlist Search Pointer (SP_SRP)

	Contents	Number of Bytes
(1) SPI_SA	Start Address of Playlist Information	4

(1) SPI_SA

Describes the Start Address of the corresponding Stream Playlist Information, with RBN from the first byte of this SPLT.

2.1.3.3 Stream Playlist Information (SPI)

	Contents	Number of Bytes
(1) PE_Ns	Number of Playlist Entries	2
(2) SPL_CREATE_TM	Creation Time of this SPL	5
(3) SPL_NAME	Stream Playlist Name	variable

(1) PE_Ns

Describes the Number of playlist entries of which this playlist consists. The maximum allowed number of playlist entries per playlist is TBD. PE_Ns also informs, which and how many of the subsequent PEs belong to this playlist.

(2) SPL_CREATE_TM

Describes the creation time of this playlist in STRR's Date and Time Describing format TBD.

(3) SPL_NAME

Describes the Stream Playlist Name as a variable length string of characters from the character set identified by SPLN_CHRS of SPLT_GL.

2.1.3.4 Playlist Entry Information

	Contents	Number of Bytes
(1) PE_ST_N	Index of Stream Title	2
(2) PE_S_SCR	Start SCR	6
(3) PE_E_SCR	End SCR	6
	Total	14

(1) PE_ST_N

Describes the index of the Stream Title to be played back for this PE.

(2) PE_S_SCR

Describes the Extended SCR value of the first application packet to be played back.

(3) PE_E_SCR

Describes the Extended SCR value of the last application packet to be played back.

~~DVD Stream Recording~~

13

THOMSON multimedia Confidential 7

2.1.4 Housekeeping General Information (HKP_GI)

	Contents	Number of Bytes
(1) HAE_Ns	Number of Housekeeping Address Entries	2
(2) HKPI_EA	End address of HKPI	4
(3) HKP_TSCAL	Time Scale Factor	1
	Total	7

(1) HAE_Ns

Describes the number of housekeeping address entries contained in this HKPI. The maximum allowed number of housekeeping address entries is TBD.

(2) HKPI_EA

Describes the End Address of this HKPI with RBN from the first byte of this HKPI.

(2) HKP_TSCAL

Describes the time scaling used within this HKPI. Details of time scaling are TBD.

2.1.5 Housekeeping Address Table (HAT)

The purpose of this table is to provide all necessary information so that given playlist entries are efficiently translated into disc address pairs (from-to). Details of HAT are TBD.

2.2 Application Private Data

APD, if it exists, consists of three kinds of information, namely Application Private Data General Information (APD_GI), a set of one or more Application Private Data Search Pointer (APD_SRP), and a set of one or more Application Private Data Area (APDA). If any Application Private Data exists, these three kinds of information shall all mandatorily be recorded and stored in the APPLICAT.IFO file in this order.

NB: Unlike in the "DVD Specification for Read-Only Disc Part 3 VIDEO SPECIFICATION", where each table within Navigation Information shall be aligned on a sector boundary, there is no such restriction in Stream Recording.




Figure 2-2 Application Private Data

2.2.1 Application Private Data General Information

	Contents	Number of Bytes
(1) APDA_Ns	Number of Application Private Data Areas	1
(2) APD_EA	End Address of Application Private Data	4
(3) APDA_SRV_ID	APD Area Service ID	APDA_Ns x 4

- (1) APDA_Ns
Describes the number of Application Private Data Areas, into which this APD is organized.
- (2) APD_EA
Describes the end address of APD with RBN from the first byte of the APD.
- (3) APDA_SRV_ID
Describes a Service ID for each of the Application Private Data Areas to follow. For details of Service ID, see Annex A.

2.2.2 Application Private Data Search Pointer

	Contents	Number of Bytes
(1) APDA_SA	Start address of APDA	4

(1) APDA_SA

07-09-1998

'98 17:26

TCE PATENTS GERM

EP98250316.1

TCE PATENTS GERMANY

S.2

DESC

~~DVD Stream Recording~~

X715

8/26/1998

~~THOMSON multimedia Confidential~~

Describes the start address of APDA with RBN from the first byte of APD.

2.2.3 Application Private Data Area

	Contents	Number of Bytes
(1) APDA	Application Private Data Area	Variable

(1) APDA

Describes the Application Private Data.

3 Stream Data Format

Stream Data according to this Specification consists of one or more „Stream Objects“ (SOBs) which are each stored as a „Program stream“ as described in [MPEG-2 Systems]. A SOB has the following restrictions:

- 1. Each SOB shall be terminated by a program_end_code.
- 2. The value of the SCR field in the first pack of each SOB may be non-zero.

A SOB contains the Stream Data packed into a sequence of „Stream Packs“ (S_PCKs).

The transfer rate of SOBs shall obey the restrictions listed in Table 3-1.

Table 3-1 : Restrictions on transfer rate of Stream Data

Minimum Transfer rate	TBD
Maximum Transfer Rate	TBD

Stream Data described under this Specification are organized as one elementary stream and are carried in PES packets with a stream_id of of private_stream_1. In some other formats of the DVD family, private_stream_1 is also used to carry several kind of non-MPEG AV Presentation Data. As a means of distinction among these, the first byte of the data area of each packet is used as „sub_stream_id“. DVD Stream Recording, although already separated by the use of a different directory for its data, shares this principle, i.e. the first byte of data area is used as a sub_stream_id and is entered as a new, unique value of TBD designating the subsequent payload as „Stream Recording Data“.

3.1 Stream Object

A stream Object is composed of one or more Stream Packs (S_PCKs) as shown in Fig 3-1




Figure 3-1 : Structure of a Stream Object

Because the length of a SOB is basically arbitrary, the last S_PCK of a SOB might employ padding in one of two different ways. For details see Section ??.


3.2 Stream Pack

Stream Packs are „Program Stream Packs“ in the sense of [MPEG2 System] and comply with all rules given there. The pack length is 2048 bytes (one LB) and a pack is recorded in one LB.

DVD Stream Recording

19 17 THOMSON multimedia Confidential ?

A Stream Pack consists of one pack header, followed by zero or one system header, and followed by one Stream Packet (S_PKT). An extra padding packet will not be employed, as shown in Figure 3-2.



* may or may not exist

Figure 3-2 : Structure of a Stream Pack

A system header is included exactly in those S_PCKs, which are the first S_PCK of a SOB. When a system header is included, the length of the remaining Stream Pack content is 2010 bytes, when it is not included, the length of Stream Pack content is 2034 bytes.

In Stream recording, the application performs its own padding, so that the pack length adjustment methods of DVD-ROM Video or RTRW need not to be used. In Stream recording it is safe to assume, that the Stream packets will always have the necessary length.

3.2.1 Pack Header

Table 3-3 : Pack header

Field	Number of bits	Number of bytes	Value	Comment
Pack start code	32	4	0000 01BAh	
'01'	2	6	provider defined	01b
SCR_base[32..30]	3			(Note 1)
marker bit	1			1
SCR_base[29..15]	15			
marker bit	1			1
SCR_base[14..0]	15			
marker bit	1	3	01 3883h	1
SCR_extension	9			
marker bit	1			1
program_mux_rate	22			mux_rate = 8Mbps (Note 2)
marker bit	1	1	F8h	1
marker bit	1			1
reserved	5	1	F8h	11111b
pack_stuffing_length	3			no stuffing length = 000b

Note 1: „SCR_base[32]“ shall be set to ZERO.

Note 2: „program_mux_rate“ shall be set to 8Mbps.

DVD Stream Recording

20 18

THOMSON multimedia Confidential?

3.2.2 System Header

Table 3-4 : System header

Field	Number of bits	Number of bytes	Value	Comment
system_header_start_code	32	4	0000 01BBh	
header length	16	2		
marker_bit	1	3	809C41h	1
rate_bound	22			mux_rate = 8Mbps
marker_bit	1			1
audio_bound	6	2	0	No audio streams
fixed_flag	1		0	Variable bit rate
CSPS_flag	1		1 or 0	
system_audio_lock_flag	1		1	
system_video_lock_flag	1		1	1
marker_bit	1	1	1	1
video_bound	5		0	No video streams
packet_rate_restriction_flag	1		0 or 1	
reserved_bits	7		7Fh	
stream_id	8	1	??	??
'11'	2	2	11b	
P-STD_buf_bound_scale	1		1	buf_size x 1024 bytes
P-STD_buf_size_bound	13		232	buf_size = 237568 bytes
stream_id	8	1	??	??
'11'	2	2	11b	
P-STD_buf_bound_scale	1		0	buf_size x 128 bytes
P-STD_buf_size_bound	13		32	buf_size = 4096 bytes
stream_id	8	1	1011 1101b	private_stream_1
'11'	2	2	11b	
P-STD_buf_bound_scale	1		1	buf_size x 1024 bytes
P-STD_buf_size_bound	13		58	buf_size = 55392 bytes
stream_id	8	1	1011 1111b	private_stream_2
'11'	2	2	11b	
P-STD_buf_bound_scale	1		1	buf_size x 1024 bytes
P-STD_buf_size_bound	13		2	buf_size = 2048 bytes

3.3 Stream Packet

In Stream Packets, no stuffing takes place and each Stream packet has just DTS, no PTS. Packet header size therefore is 14 bytes constant.

DVD Stream Recording

24.19 THOMSON multimedia Confidential?

3.3.1 Packet Header

Field	Number of bits	Number of bytes	Value	Comment
packet start code prefix	24	3	00 0001h	
stream_id	8	1	1011 1101b	private stream 1
PES_packet_length	16	2		
'10'	2	3	10b	
PES_scrambling_control	2			TBD
PES_priority	1		0	no priority
data_alignment_indicator	1		0	not defined by descriptor
copyright	1		0	not defined by descriptor
original_or_copy	1		0	copy
PTS_DTS_flags	2		10b	
ESCR_flag	1		0	no ESCR field
rate_flag	1		0	no ES rate field
DSM_trick_mode_flag	1		0	no trick mode field
additional_copy_info_flag	1		0	no copy info field
PES_CRC_flag	1		0	no CRC field
PES_extension_flag	1		0	no extension
PES_header_data_length	8	5	5	
'0001'	4		Provider defined	
DTS[32..30]	3			
marker bit	1			
DTS[29..15]	15			
marker bit	1			
DTS[14..0]	15	0 to 7		
marker bit	1			
stuffing byte	-			
Private data area				
stream_id	8	1	TBD	
Stream data area				

3.3.2 Stream Data area

The Stream data area inside a Stream Packet consists of an application header, an application header extension, and a sequence of application packets, each prefixed by an application packet timestamp.

DVD-Stream Recording

PGF-3 - 8/28/1998

20

THOMSON multimedia Confidential?

3.3.2.1 Application Header

Field	Number of bits	Number of bytes	Value	Comment
(1) MAX_BITRATE	32	4		
(2) SMOOTH_BUF_SIZ	16	2	3540 bytes	
(3) TS_REF_CL_FREQ	32	4	27 MHz	
(4) AP_PKT_LEN	16	2		
(5) TS_LEN	8	1	'4'	
(6) AP_PKT_Ns	8	1		
(7) START_OF_STR	1	1	0b or 1b	
(8) END_OF_STR	1		0b or 1b	
reserved	6			
	Total	15		

(1) MAX_BITRATE

Describes the output bitrate parameter of the leaky bucket flow control model in Mbps.

(2) SMOOTH_BUF_SIZ

Describes the buffer size parameter of the leaky bucket flow control model.

(3) TS_REF_CL_FREQ

Describes the reference clock frequency of the packet arrival/delivery timestamp.

(4) AP_PKT_LEN

Describes the length of the application packet.

(5) TS_LEN

Describes the length of the timestamp field.

(6) AP_PKT_Ns

The number of application packets in this DVD pack.

(7) START_OF_STR

When set to '1', this packet is the first DVD pack in the stream.

(8) END_OF_STR

When set to '1', this packet is the last DVD pack in the stream.

3.3.2.2 Application Header Extension

The application header extension consists of a list of entries, where there is exactly one entry for each transport layer packet. These bytes are used to store information that may differ from packet to packet.

The total length of the application header extension shall be 46 bytes. The first 'AP_PKT_Ns' entries of these shall carry valid data. Unused list entries may carry undefined values.

The total length of 'application header' and 'application header extension' shall be 61 bytes.

Field	Number of bits	Number of bytes	Value	Comment
(1) AU_START	1			
(2) AU_END	1	1		
(3) reserved	4			
(4) COPYRIGHT	2			

(1) AU_START

When set to '1', indicates that the associated application packet contains a random access entry point into the stream

(2) AU_END

When set to '1', indicates the associated application packet is the last packet of a random access point.

(4) COPYRIGHT

Describes the copyright status of the associated application packet. Details are TBD

3.3.2.3 Time Stamps

The data stream contains time stamps, e.g. within the data packets.

List of Abbreviations

LB.....Logical Block
RBN.....Relative Byte Number

RBP.....Relative Byte Position
RLBN.....Relative Logical Block Number

THOMSON multimedia
CORPORATE RESEARCH
HANNOVER

Page 1

Date

Sep 4, 1998

Index

of 1 pages

Name

Harald SCHILLER

THOMSON multimedia CONFIDENTIAL

ISO 9001
certified

22

ADDENDUM ON DVD STREAM RECORDING SPECIFICATION (DRAFT) V.0.1
RE-TIMESTAMPING

Stream recording assumes an "application Device" (e.g. set top box) connected to a DVD Streamer. They are connected e.g. via IEEE1394, which in its transmitting and receiving firmware contains means to timestamp data, and to strip off these timestamps again, using them for timing regeneration. The effect of this is that between the input of 1394 and its output, it behaves like a constant delay system. Normally, the dvd Streamer then has a similar task, and will be using similar method: the streamer must regenerate the timing of data packets as it was upon recording, when these packets are played back, so that between recording and playback, it also behaves like a constant delay system.

The streamer, too, can use timestamps and strip them off again, using them for timing regeneration.

So, in total, we have an "in series" connection between two time stamping /&time regeneration mechanisms. this series connection involves some jitter accumulation.

Now, the invention proposes that the application device itself, before sending the data thru the 1394, adds time stamps to the data packets. these timestamps have the meaning of "departure time" rather than arrival time. these time stamps then go thru the 1394 "unnoticed" (i.e. from 1394 point of view they are part of the payload), and on the other end of the chain, these timestamps can be used when the dvd streamer plays back a stream. The advantage is that there is just one timing/regeneration process involved, no jitter accumulation takes place.

Claim

1. Method for timestamping a bitstream to be recorded or for
using timestamps recorded on a storage medium, e.g. a DVD
5 recorder, wherein a device outputting said bitstream to
be recorded adds said timestamps to data packets of said
bitstream and wherein said timestamps represent a depar-
ture time instead of an arrival time, and wherein the
bitstream passes through an IEEE1394 connection for which
10 said timestamps belong to the payload and said timestamps
are also used when replaying said bitstream.

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)